

KCC 4773 (K-C 17,181)  
PATENT

AMENDMENTS TO THE CLAIMS

This listing will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Canceled).
2. (Currently amended) The garment of claim [[1]] 27, wherein the multi-directional stretchable loop ~~material~~ fastening component is elastomeric during use in both the first and second directions.
3. (Currently amended) The garment of claim [[1]] 27, wherein the multi-directional stretchable loop ~~material~~ fastening component comprises a nonwoven web stretch bonded to an elastomeric film.
4. (Currently amended) The garment of claim [[1]] 27, wherein the multi-directional stretchable loop ~~material~~ fastening component comprises a mechanically prestrained composite.
5. (Currently amended) The garment of claim [[1]] 27, wherein the multi-directional stretchable ~~landing member loop~~ fastening component and ~~closure member~~ hook fastening component provide shear strength values of about 3500 grams or less in each of the first and second directions.
6. (Currently amended) The garment of claim [[1]] 5, wherein the multi-directional stretchable ~~landing member loop~~ fastening component and ~~closure member~~ hook fastening component provide shear strength values of about 3000 grams or less in each of the first and second directions.

KCC 4773 (K-C 17,181)  
PATENT

7. (Currently amended) The garment of claim [[1]] 6,  
wherein the multi-directional stretchable ~~landing-member~~ loop  
fastening component and ~~closure-member~~ hook fastening component  
provide shear strength values of about 2500 grams or less in  
5 each of the first and second directions.

8. (Currently amended) The garment of claim [[1]] 27,  
wherein the hook ~~material~~ fastening component is stretchable.

9. (Canceled).

10. (Currently amended) The disposable absorbent article  
of claim [[9]] 28, wherein the multi-directional stretchable  
~~landing-member~~ loop fastening component and ~~closure-member~~ hook  
fastening component provide shear strength values of about 1500  
5 to about 3500 grams in each of the first and second directions.

11. (Currently amended) The disposable absorbent article  
of claim [[9]] 10, wherein the multi-directional stretchable  
~~landing-member~~ loop fastening component and ~~closure-member~~ hook  
fastening component provide shear strength values of about 1500  
5 to about 3000 grams in each of the first and second directions.

12. (Currently amended) The disposable absorbent article  
of claim [[9]] 11, wherein the multi-directional stretchable  
~~landing-member~~ loop fastening component and ~~closure-member~~ hook  
fastening component provide shear strength values of about 1500  
5 to about 2500 grams in each of the first and second directions.

13. (Currently amended) The disposable absorbent article  
of claim [[9]] 28, wherein the multi-directional stretchable  
~~landing-member~~ loop fastening component comprises a neck-  
stretched elastic laminate.

KCC 4773 (K-C 17,181)  
PATENT

14. (Withdrawn) The disposable absorbent article of claim 9, wherein the multi-directional stretchable landing member comprises a creped-stretched elastic laminate.

15. (Withdrawn) The disposable absorbent article of claim 9, wherein the multi-directional stretchable landing member forms part of the outer layer.

16. (Currently amended) The disposable absorbent article of claim [[9]] 28, wherein the multi-directional stretchable ~~landing member~~ loop fastening component comprises side panels of the body.

17. (Withdrawn) The disposable absorbent article of claim 9, wherein the multi-directional stretchable loop material comprises a nonwoven web stretch bonded to an elastomeric film.

18. (Withdrawn) The disposable absorbent article of claim 9, wherein the multi-directional stretchable loop material comprises a mechanically prestrained composite.

19. (Canceled).

20. (Withdrawn) The disposable absorbent article of claim 19, wherein the multi-directional stretchable loop fastening component comprises a nonwoven web stretch bonded to an elastomeric film.

21. (Withdrawn) The disposable absorbent article of claim 19, wherein the multi-directional stretchable loop material comprises a mechanically prestrained composite.

22. (Currently amended) The disposable absorbent article of claim [[19]] 29, wherein the multi-directional stretchable ~~landing member~~ loop fastening component and ~~closure member~~ hook fastening component provide shear strength values of about 1500  
5 to about 3000 grams in each of the first and second directions.

KCC 4773 (K-C 17,181)  
PATENT

23. (Currently amended) The disposable absorbent article of claim [[19]] 22, wherein the multi-directional stretchable ~~landing member loop fastening component~~ and ~~closure member hook fastening component~~ provide shear strength values of about 1500  
5 to about 2500 grams in each of the first and second directions.

24. (Withdrawn) The disposable absorbent article of claim 19, wherein the multi-directional stretchable landing member forms part of the outer layer.

25. (Currently amended) The disposable absorbent article of claim [[19]] 29, wherein the multi-directional stretchable ~~landing member loop fastening component~~ comprises side panels of the body.

26. (Currently amended) The disposable absorbent article of claim [[19]] 29, wherein the hook ~~material~~ fastening component is stretchable.

27. (New) A garment for personal wear, comprising:  
a body having first and second end regions;  
a mechanical fastening system disposed on the body, the  
mechanical fastening system comprising:  
5 a multi-directional stretchable loop fastening component  
disposed in the first end region of the body, said loop  
fastening component comprising a nonwoven loop material secured  
to an elastomeric substrate, said loop fastening component  
being extensible during use in first and second substantially  
10 perpendicular directions generally within the plane of said  
loop fastening component and being elastomeric during use in at  
least one of said first and second directions, and  
a hook fastening component disposed in the second end  
region of the garment body and comprising a hook material

KCC 4773 (K-C 17,181)  
PATENT

15 adapted to refastenably engage the multi-directional stretchable loop fastening component;

wherein the loop fastening component and the hook fastening component provide shear strength values of less than 3900 grams in each of said first and second directions.

28. (New) A disposable absorbent article for personal wear, comprising:

a body having first and second end regions and comprising a liquid permeable inner layer, an outer layer in opposed  
5 relation with the inner layer, and an absorbent layer disposed between the inner layer and the outer layer;

a mechanical fastening system disposed on the body, the mechanical fastening system comprising:

a multi-directional stretchable loop fastening component  
10 disposed in the first end region of the body, said loop fastening component comprising a nonwoven loop material secured to an elastomeric substrate, said loop fastening component being extensible during use in first and second substantially perpendicular directions generally within the plane of said  
15 loop fastening component and being elastomeric during use in at least one of said first and second directions, and

a hook fastening component disposed in the second end region of the body and comprising a hook material adapted to refastenably engage the multi-directional stretchable loop  
20 fastening component;

wherein the multi-directional stretchable loop fastening component and the hook fastening component provide shear strength values of about 1500 to about 3900 grams in each of the first and second directions.

KCC 4773 (K-C 17,181)  
PATENT

29. (New) A disposable absorbent article for personal wear, comprising:

5 a body having first and second end regions and comprising a liquid permeable inner layer, an outer layer in opposed relation with the inner layer, and an absorbent layer disposed between the inner layer and the outer layer;

a mechanical fastening system disposed on the body, the mechanical fastening system comprising:

10 a multi-directional stretchable loop fastening component disposed in the first end region, said loop fastening component comprising a nonwoven loop material secured to an elastic substrate and being elastomeric during use in first and second substantially perpendicular directions generally within the plane of said loop fastening component, and

15 a hook fastening component disposed in the second end region and comprising a hook material adapted to refastenably engage the multi-directional stretchable loop fastening component;

20 wherein the multi-directional stretchable loop fastening component and the hook fastening component provide shear strength values of about 1500 to about 3500 grams in each of the first and second directions.